# **Graphic Touchscreen Interfaces...** *at Text Display Prices*





# KEP Advantages reasons to buy / partner with us:

- Graphic Touchscreen Interfaces at Text Display Prices.
- Same day order shipment.
- One day repair for units in warranty.
- Programming cable included at no extra charge.
- Easy Set-up with Easybuilder Software included at no extra charge.
- · Connects directly to most PLC's.
- High Noise Immunity.
- Free technical support.
- OEM programs available. This includes developing software, drivers, customer overlays, etc.
- Value added integration of PLC based systems.
- Fully inspected and tested at factory.
- ISO 9001 certified facility
- 1 year warranty

# **Ordering Information**

## **MMI Touch Panels**

Part Number	Description
MMI-720	Graphic Interface with 5.7" blue, 4 grey scale, LCD display and Touchscreen
MMI-730T	Graphic Interface with 5.6", 256 color TFT display and Touchscreen
MMI-730T-E	Graphic Interface with 5.6", 256 color TFT display with Ethernet and Touchscreen
MMI-750T	Graphic Interface with 5.7" TFT, 256 color display and Touchscreen
MMI-850T	Graphic Interface with 7.7" TFT, 256 color LCD display and Touchscreen
MMI-1500T	Graphic Interface with 10.4" Color LCD Display & Touchscreen, Expanded Graphic Features and Centronics Printer Port
OPTIONS	Consult factory for additional ordering options

#### Cables

Consult factory for detailed list of available cables.

## **Kessler-Ellis Products**

10 Industrial Way East Eatontown, NJ 07724 Phone: (732) 935-1320 • (800) 631-2165 Fax: (732) 935-9344

### **General Specifications**

	-
Input Power:	24 VDC ± 5%
Approvals:	UL, CE
Environmental:	NEMA4/IP65 front panel
Operating Temp.:	32~113° F (0~45° C)
Humidity:	10-90% RH

Hardware Specifications		
Display:	MMI-720:	5.7" blue mode LCD 5.6" TFT 256 color LCD
	MMI-750T/750T-E.	5.7" color TFT
	MMI-850T:	7.7" color TFT
	MMI-1500T:	10.4" color TFT
Resolution:	MMI-720/750T:	320(W) x 240(H) pixels
	MMI-730T/730T-E:	320(W) x 2234(H) pixels
	MMI-850T:	640(W) x 480(H) pixels
	MMI-1500T:	640(W) x 480(H) pixels
Backlight:	CCFT (w/ auto shutdown)	
Touch Panel:	resistive type, audible feedback on touch	
Serial Port:	RS-232 x 1; RS-485 x 1	
Memory:	4MB DRAM, 1MB flash memory (2MB optional	
Parallel Port:	Centronic printer port (MMI-1500/MMI-850 only)	

#### **Functional Specifications**

Screen Editor:	EasyBuilder setup software for Windows™
Type of Objects:	Line, Rectangle, Ellipse, Arc, Polygon, Text, Scale, Shape, Bitmap, Bit Lamp, Word Lamp, Set Bit, Set Word, Toggle Switch, MultiState Switch, Function Button, Numeric Input, Numeric Display, ASCII Input, ASCII Display, XY Move, Animation, Spot Move Animation, Popup Window on Bit, Popup Window on Register, Alarm Display, Trend Graph, XY Plot, BarGraph, Meter, Scrolling, Alarm, Event Display, Recipe Transfer (requires option card), PLC Controls Screen, backlight, printer, Data Transfer
PLC Drivers:	Consult factory for detailed list
Printer Support:	Simple ASCII, EPSON ESC/P2, HP PCL/ (Simple page mode) or compatible

#### Dimensions

MMI-720/730T/750T W = 8.03" (204mm) H = 5.91" (150mm) D= 2.95" (75mm) PCW = 7.56" (192mm) PCH = 5.43" (138mm)

#### MMI-850T

W = 9.10" (231mm) H = 6.93" (176mm) D= 2.17" (55mm) PCW = 8.75" (222mm) PCH = 6.58" (167mm)

#### MMI-1500T

W = 12.4" (315mm) H = 9.37" (238mm) D= 2.44" (62mm) PCW = 11.89" (302mm) PCH = 8.86" (225mm)



