MS846

FEATURES:

- Accommodates Flow Computer(s) and Accessories (printers, converters, etc.)
- Seamless formed in place PUR gasket assures watertight and dust tight seal
- Mounting brackets and attachment screws are provided with each enclosure
- Hinge is corrosion-resistant type stainless steel
- · Stainless Steel quick release lockable latches

Included:

Hinged cover. Base with 10-32 brass inserts, latched cover with formed in place PUR gasket, stainless hinge pin. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Height (In.): 14.0 (356mm) Width (In.): 12.0 (305mm) Depth (In.): 7 (178mm)

Materials:

Material: Polycarbonate Base color: RAL 7035 -light grey Cover color: RAL 7035 -light grey Gasket material: Polyurethane

Test Spec:

Construction meets NEMA/EEMAC Type 1, 2, 3, 4, 4X, 12 & 13 UL® 508A listed; Type 1, 2, 3, 3R, 4, 4X, 12, and 13 CSA-C22 No. 14; Type 1, 2, 3, 3R, 4, 4X, 12, and 13 IEC60529 Type IP66

Temperature:

Short Term: -40 to 250°F (-40 to 140°C) Continuous: -40 to 175°F (-40 to 80°C)

Rating

Ingress protection (EN 60529): IP66; IP67 NEMA Class NEMA 4, 4X, 12 and 13 Impact Resistance (EN 62262): IK09; Electrical insulation: Not insulated Halogen free (DIN/VOE 04 72, Part 815): 1 UV resistance: UL 508

Flammability Rating: UL 508

Glow Wire Test (IEC 695-2-1) °C: 960 °C

Certificates:

ARCA_ Certificate of Compliance

Large NEMA 4X Housing with Hinged Cover



Ordering Information:

Part Number:

MS846NEMAST4X0QR - enclosure with no cutouts

MS846NEMAST4X1QR - enclosure with 1 cutout for ST series MS846NEMAST4X2QR - enclosure with 2 cutouts for ST series MS846NEMAST4X3QR - enclosure with 3 cutouts for ST series

NOTE: QR in part number depicts Quick Release Latches (std)

<u>Options</u>

SPA - Sub-Panel (aluminum) SPP - Sub-Panel (PVC) SPS - Sub-Panel (painted steel)

DR1 - Single DIN Rail Installed for accessory mounting

DO - Duplex Outlet

CB16 - Dual Circuit Breaker- 16 AMP

TB - Terminal Block

TB3 - 3 Position Fused Terminal Block

PW - Internal Pre-wired by KEP (Please provide desired wiring sketch)

A - Assembled at KEP

Consult factory for custom conduit hole, fitting and factory wiring options.



10 Industrial Way East, Eatontown, NJ 07724 800-631-2165 • 732-649-7100 • Fax 732-649-7099 • https://www.kep.com

