
# **Panel Mount Impact Dot Matrix Printer**

### **Features**

- Ultra small-sized rack mounting dot matrix printer
- Extremely light weight
- · High speed printing
- · Paper end detecting function
- Auto loading function
- RS-232C Serial Interface



#### **DESCRIPTION:**

The PMi920 is built for panel mounting. The printer also incorporates specialized auto loading and a paper end sensor for optimum efficiency. Robust construction gives total reliability, with a MCBF of at least 1.0 million lines. An integral memory switch increase flexibility and functionality still further.

- · Compact and reliable
- Panel mounting
- · Auto loading

#### **SPECIFICATIONS**

**Printing Technology** Serial dot impact Print Speed (maximum) 150 mm /sec. **Print Width (maximum)** 57.5 mm Media Width (min to max) 57.5 mm Media Thickness (min to max) 130 µm

Roll Size (max), Core Size 69 mm outside diameter Size (W x D x H) and Weight 106x180x88 mm, 0.47 Kg

**Barcodes** None **Power supply** 5 VDC

1.5 Million lines Reliability **EMC** and safety standards FCC class B

**Number of columns** Up to 40 (1.08 x 2.4 mm) Line spacing Character: 3.52 mm, Graphic:

2.4 mm

Input buffer 2K bytes 0 to +40°C **Operation environment** 

Storage environment -20 to +60°C (10% to 90% RH

non condensing)

Interface Serial (RS-232C compliant)



Standard Panel Mount




-N Option, Nema 4X Enclosure



**Custom Configurations Available** 



# Sample Ticket:






Kessler-Ellis Products 10 Industrial Way East Eatontown NJ 07724 800-631-2165 or 732-935-1320

www.kep.com

# Mounting:



## **How To Order:**

EXAMPLE	PMi920 N	
Series		
PMi920 =	Panel Mount; Impact Receipt Printe Serial Interface	er;
Options —		
N = NEMA 4X Wall Mount Enclosure with		

sub-panel & duplex outlet

#### **Accessories**

PMi920-INK = Printer Ink Ribbons, 6/ctn

PMi920-PR1P = Paper 2.25" x 60', 1-ply, 20 rolls/case

PMi920-PR2P = PAPER 2.25" x 3.125" x 95',

2 PLY 50 rolls/case