

PMt2212

Panel Mount Thermal Receipt Printer

Features

- 2.24" Thermal Line Printer
- Easy Paper Loading
- High Print Speed
- RS232 Interfaces
- 24VDC Input Power
- Uses TP58-80 Paper Roll

Description:

The PMt2212 is a small format, thermal panel mount printer with easy paper loading. The compact design and unique attachment make installation a simple matter. The PMt2212 printer is a perfect companion for our flow computers and batch controllers and they are ideal for systems that require transaction printing.



SIZE

Dimensions (WxDxH) 84.8 x 84.8 x 67.7 mm
Weight 160 g

GENERAL

Model PMt2212
Print Method Thermal Line Printing
Dots Per Line 384
Dot Pitch 8 dots/mm
Dot Size 0.125x0.12 mm
No. Of Columns 48
Printing Width 48 mm
Print Speed 50 mm/s
Character Size 12x24, 8x16 dots
Character Set ASCII, GB18030, Big5
Paper Loading Easy Paper Loading

POWER SUPPLY

Power Requirement 9-35 VDC, 2.0 Amps

COMMUNICATION

Interface RS232
Data Buffer 8 KB
Flash 64 KB

PAPER

Paper Type Thermal Roll Paper
Width 58mm
Diameter 50mm
Thickness ~80µm



ENVIRONMENTAL

Operating Condition 5° to 50°C, 10 to 85% RH
Storage Condition -20° to 60°C, 5 to 90% RH


RELIABILITY

Printhead 100 km Feed Length




10 Industrial Way East, Eatontown NJ 07724 • 800-631-2165 or 732-649-7100 • www.kep.com

Sample Ticket:




Mounting:



10 Industrial Way East
 Eatontown NJ 07724
 800-631-2165 or 732-649-7100

www.kep.com

How To Order:



Accessories

- P2212-PC-FLL24 = Power Cable, Flying Leads, 24" Long
- PMt2212-RS232DB9-L24 = 24" Serial cable terminated with mating serial connector on printer end; DB-9 male connector on other end
- PM2212PR = Paper Roll for PMt2212 Printer; Single-ply Thermal Paper (Pack of 50)
- PM2212PR-AB = Paper Roll for PMt2212 Printer; Thermal Paper with Adhesive Backing (Pack of 50)