

CA-285

RS-422/485 to RS-232 Interface Converter

Features

- User Selectable RS-422 or RS-485
- RS-485 User Selectable 2 or 4-Wire Operation
- Intelligent Control of RS-485 Transmitter and Receiver
- Td and Rd LED
- DTE/DCE Compatible
- Data Rates up to 64k BPS
- Connects to Standard PC Compatible 25 Pin RS-232 Port

DESCRIPTION:

The CA-285 is a unique interface converter that can be configured by the user to convert either RS-422 or RS-485 to RS-232. When operating in RS-485 mode, the CA-285 has an "intelligent" mode which provides control of the RS-485 line.

When configured to operate as an RS-232 to RS-422 interface converter, the CA-285 converts full duplex data, Td and Rd, between RS-232 and RS-422.

As an RS-232 to RS-485 converter, the unit can be configured for either 2 or 4-wire operation. In either mode, the CA-285 allows control of the transmitter so that multi-dropped operation can be accommodated. The CA-285 can be configured to control its data flow in one of two ways. The first is via the use of RTS, pin 4, of the RS-232 port. In this case, the RS-485 transmitter will turn ON when RTS is turned on. When RTS is OFF, the CA-285 is in the receive mode. In the 4-wire mode, the receiver is always on. The second method of controlling the RS-485 transmitter is to turn it on when Td data is applied to the RS-232 port. (recommended with KEPServer)

The receiver also operates differently depending on whether the mode is 2 or 4-wire. In the 2-wire mode, when no data is received by the RS-232 receiver, the RS-485 receiver is switched ON. When data is detected for transmission, the receiver is switched OFF. In the 4-wire mode, the RS-485 receiver is constantly ON while the transmitter is switched as required.

The CA-285 is equipped with a five position dip switch that is used to select the following:

RS-422 mode: 4-wire
RS-485 mode: 2-wire
RS-485 mode: 4-wire
RS-485 mode: controlled by RTS
RS-485 mode: controlled by data
220 ohm terminator: in or out

The CA-285 is also equipped with a DTE/DCE switch to allow reversing pins 2 and 3 on the RS-232 interface. Td and Rd LED indicators help verify operation.



SPECIFICATIONS:

Interface:	RS-232, conforms to CCITT V.24; pins 2 and 3 (transmit/receive data) switch selectable, pin 4 (RTS) tied to pin 5 (CTS), pins 6 (DSR), 8 (DCD) and pin 20 (DTR) are connected together; RS-422 or RS-485, selectable
Connectors:	RS-232, DB-25 male, RS-422/485, 5-position terminal block
Indicators:	2 LEDs, Td and Rd
Switches:	DTE/DCE switch selectable for reversing Td and Rd; 5-position dip switch set RS-422/485 operation and termination
Data Rate:	0 to 64k bps
MTBF:	596,000 hours
Power:	115 VAC at 60 Hz (Wall plug power adapter with 6' cable provided)
Size:	0.875"H x 2"W x 3.5" D
Operating Temp.:	32 to 122°F (0 to 50°C)
Humidity:	5 to 95% RH (non-condensing)

Ordering Information

EXAMPLE CA285
Series _____

CA-285 RS-422/485 to RS-232 Communication Adaptor