



FTRV7.E81696 Enclosures for Use in Hazardous Locations Certified for Canada

[Page Bottom](#)

Enclosures for Use in Hazardous Locations Certified for Canada

[See General Information for Enclosures for Use in Hazardous Locations Certified for Canada](#)

ADALET/SCOTT FETZER CO

E81696

4801 W 150TH ST
CLEVELAND, OH 44135 USA

Class I, Groups A, B, C and D; Class II, Groups E, F and G; Class III.

Cat. No. XJXCX may be followed by N4.

Class I, Groups B, C and D; Class II, Groups E, F and G; Class III.

Cat. No. S5568.

Cat. Nos. S-4926, -4927, -5564, XCE, XCEX-041604, -060804, -060805, -060806, -061105, -061204, -061206, -061305, -071004, -071006, -071805, -080804, -080806, -080806N4-S6005, -080806N4-S6006, -080808, -081004, -081006, -081006N4-S6008, -081008, -081204, -081206, -081208, -091105, -101004, -101006, -101008, -101206, -101404, -101406, -101406N4-S6119, -101408, -101410, -121204, -121206, -121206N4-S6011, -121206N4-S6014, -121208, -121804, -121806, -121806N4-S6018, -121808, -122005, -122404, -122406, -122408, -122408N4-S6019, -122410, -123006, -123604, -123606, -123608, -124608, -141404, -141406, -141408, -142210, -142213, -142806, -161604, -161606, -161608, -162406, -162408, -162410, -162806, -163010, -163406, -164610, -181804, -181806, -181808, -181808 N4 S7619, -182406, -182408, -182410, -183008, -183608, -183610, -242408, -242410, -243008, -243608, -243610, XCE061105N4-S6697, -081206N4-S6698, -323612N4-S7066, -S7586, -S7587, -S7594, -S8049, -S8050, -S8116, -S8684, -S8685, -S8690, -S9296, -S9297, -S9380, -122408N4-S5983, -242408N4-S6824, -244806N4, -242408N4-S6839, XCMRSG, XCE060805N4-S7371, XCMRSK, XMRSC, XMRSF, XMSB, XMSD, XMSH. May be followed by N4, may be followed by Q; XCE, XCEX may be followed by N4X.

Cat. Nos. XCESX-101408, -121208, -122410, -242410 and -243610. May be followed by -T. May be followed by N4 (Type 4). When stainless steel bolts are used, may be followed by N4X (Type 4x).

Cat. No. XCE080808-S7093, may be followed by N4, may be followed by N4X.

Cat. No. XCE 204806 may be followed by -N4.

Cat. Nos. XCESX-101408, -121208, -122410, -242410, -243610. May be followed by -T. May be followed by N4 or N4X.

Cat. Nos. XCBSN, XCMRSP, XMRSO, XMSQ, XPB1, XPB2, followed by 12, 18, 24, 30, 36, may be followed by 1 or 3, may be followed by N4, may be followed by Q.

Cat. No. XCB followed by A, B, C, D, E, F or G; Cat. No. XCBS, followed by L or M.

These enclosures may be provided with the suffix -N4.

Cat. No. XDHM or XIHM followed by -DC, -DGC, -DJC, -FC, -FGC, -FJC or -MC may be followed by X; Cat. No. XIHMK, followed by -FC, or -FGC may be followed by X.

Cat. No. XDH, followed by -FC, -FGC, -FGCC, -DC, -DGC or -DGCC, may be followed by X, followed by 2 or 3, followed by A, B, C, D or E, followed by N4 or N4X.

XJ Series enclosures, Cat. Nos. XJD, XJDA, XJDFGC, XJHA, XJHB, XJHC, XJQH, XJK, XJKA, XJL, XJM, XJMA, XJMC, XJN-6, -12, XJS, XJT, XJTFCG, XJWH, XJWT, XJX may be followed by suffix GC, may be followed by suffix H, HX or X, may be followed by N4 or N4X.

Series XHVX followed by 121206, 121208, 121806, 121808, 122406, 122408, 122410, 123006, 123606, 123608, 124608, 141406, 141408, 142806, 161606, 161608, 162406, 162408, 162410, 162806, 163406, 164610, 181806, 181808, 182406, 182408, 182410, 183008, 183608, 183610, 242408, 242410, 243008, 243608, 243610. All numbers may be followed by -N4.

XCPX-041604, -060804, -060805, -060806, -061105, 0061204, -061206, 061305, -071004, -071006, -071805, -080804, -080806, -080808, -081004, 081006, -081008, -081204, -081206, -081208, -091105, -101004, -101006, 101008, -101206, -101404, -101406, -101408, -121204, -121206, -121208, 121804, -121806, -121808, -122005, -122404, -122406, -122408, -122410, 123006, 123604, -123606, -123608, -124608, -141404, -141406, -141408, 142806, 161604, -161606, -161608, -162406, -162408, -162410, -162806, 163406, -164610, -181804, -181806, -181808, -181808 N4 S7619, -182406, -182408, -182410, -183008, -183608, -183610, -242408, -242410, -243008, -243608, -243610. May be followed by N4 (Type 4). When stainless steel bolts are used, may be followed by N4X (Type 4X).

Cat. Nos. XDHL, XIHL, followed by -DC, -DGC, -EC, -FC or -FGC, may be followed by X, may be followed by S, may be followed by -N4 or N4X.

Cat. No. XIHS followed by -VDC, -BDGC, -BFC, -CDC, -CDGC, -CFC, -DDC, -DDGC, -DFC, -LDC, -LDGC, -LFC, -TDC, -TDGC, -TFC, -XDC, -XDGC, -XFC, -YDC, -YDGC or -YFC, may be followed by X, followed by 2, 3 or 4, may be followed by -N4 or N4X.

Cat. No. XIHNS followed by -FC, FGC, DC, or -DGC, may be followed by X.

Cat. No. XIH, followed by -FC, -FGC, -FGCC, -DC, -DGC or -DGCC, may be followed by X, followed by 2 or 3, followed by N4 or N4X; Cat. Nos. S6254 and S6288.

Cat. Nos. XDHM, XIHM followed by -DC, -DGC, -DJC, -FC, -FGC, -FJC or -MC may be followed by X; Cat. No. XIHMK followed by -FC, or -FGC may be followed by X.

Cat. No. XJANT followed by B, C, D, L, T or X, followed by 2, 3, 4 or 20, may be followed by U or P.

Cat. Nos. XJT, XJTH, XJQH followed by HL or S4455, may be followed by N4 or N4X.

Cat. Nos. XDHIFCX, XDHIFGCX, XDHIDCX, XDHIDGCX.

Class I, Groups C and D; Class II, Groups E, F and G; Class III.

Cat. Nos. XCEX081006N4-S6114, -S8810.

XJ Series enclosures, Cat. Nos. XJD, XJDA, XJDFGC, XJHA, XJHB, XJHC, XJK, XJKA, XJL, XJM, XJMA, XJMC, XJN-6, -12, XJS, XJT, XJTFGC, XJWH, XJWT, XJX may be followed by suffix GC, may be followed by suffix X, may be followed by N4 or N4X.

Cat. No. S5564, followed by -N4.

Cat. No. XCB, followed by A, B, C, D, E, F or G, followed by N4; Cat. No. XCBS followed by A, B, L or M, may be followed by Q, followed by N4, Type 4, 4X or N4X.

Cat. Nos. XCE, XCEX followed by -041604, -060804, -060805, -060805N4S7035, -060806, -061105, -061204, -061206, -061305, -071004, -071006, -071805, -080804, -080806, -080808, -081004, -081004 N4 S7620, -081006, -081008, -081204, -081206, -081208, -091105, -101004, -101006, -101008, -101206, -101404, -101406, -101408, -101410, -121204, -121206, -121208, -121804, -121806, -121808, -122005, -122404, -122406, -122408, -122410, -123006, -123604, -123606, -123608, -124608, -141404, -141406, -141408, -142210, -142213, -142806 may be followed by -T, may be followed by -N4; Cat. Nos. XCE080806N4-S6005, -080806N4-S6006, -081006N4-S6008, -101406N4-S6119, -101408N4-S4728, -163406N4-S6941.

XCEX, followed by 161604, 161606, 161608, 162406, 162408, 162410, 162806, 163406, 164606, 181804, 181806, 181808, 182406, 182408, 182410, 183008, 183608, 183610, 242408, 242410, 243008, 243608, 243610 may be followed by -T.

Cat Nos. Series XCPX followed by -041604, -060804, -060805, 060805 N4 S7035, -060806, -061105, -061204, -061206, 061305, -071004, -071006, -071805, -080804, -080806, -080808, -081004, -081004 N4 S7620, 081006, -081008, -081204, -081206, -081208, -091105, -101004, -101006, 101008, -101206, -101404, -101406, -101408, -121204, -121206, -121208, -121804, -121806, -121808, -122005, -122404, -122406, -122408, -122410, 123006, -123604, -123606, -123608, -124608, -141404, -141406, -141408, 142806, -161604, -161606, -161608, -162406, -162408, -162410, -162806, 163406, -164610, -181804, -181806, -181808, -182406, -182408, -182410, 183008, -183608, -183610, -242408, -242410, -243008, -243608 and -243610. May be followed by -T. May be followed by N4 (Type 4). When stainless steel bolts are used may be followed by N4X (Type 4X).

Cat. No XCPX-060804N4; followed by -S; followed by a four digit number. N4 designates Type 4.

Cat. Nos. XCE060804N4-S followed by a four digit number and XCEX060804N4-S followed by a four digit number.

Cat. Nos. XCMRSG, XCMRSK, XMRSC, XMRSF, XMSB, XMSD, XMSH may include suffix "Q", followed by suffix N4(+), conduit sizes 1/2 to 4 in. incl.; Cat. No. XCEQ-121808N4-S5564.

Cat. No. XB2 S6246.

Cat. No. XMMS 050704, may be followed by -N4 or N4X.

Cat. Nos. XDHMDJC-DJC, XDHMDGC-DJC, and XDHMDJC-DC.

Cat. No. XIFX followed by -030303, -030603, -030703, -030903, -031103, -031303, -031503, -031803, -032403, -033003, -033603, -040604, -041204, -060606, 060608, 061206, -070704, 1/2 to 2 in. NPT and M16 to M50 conduit sizes. +

Cat. No. XIFCX followed by -030303, -030603, -030703, -030903, -031103, -031303, -031503, -031803, -032403, -033003, -033603, -040604, -041204, -060606, 060608, 061206, -070704, may be followed by T, 1/2 to 2 in. NPT and M16 to M50 conduit sizes. +

Cat. Nos. XIFC-040604, -S5749, -S5951 may be followed by -N4, may be followed by -shaft, XIFC; Cat. Nos. XIFC030303, -030603, -030703, -030903, -031103, -031303, -031503, -031803, -032403, -033003, -033603, -033603, -S6068, -041204, -060606, -060608, -061206, -070704, may be followed by -N4; Cat. Nos. XMMSA-1, -2.

Class I, Division 2, Groups A, B, C, and D; Class III.

Cat. Nos. X2PB1-XXX-XXX, X2PB2-XXX-XXX-XXX, X2PB3-XXX-XXX-XXX, where XXX maybe any series of numbers or letters.

+ Complementary Classified under FTQH, FTQH7.

Last Updated on 2013-04-26

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".